


技术参数:

- 插芯:
- 插针数: 1
 - 额定电流: 250A
 - 额定电压: 2000V
 - 额定脉冲电压: 12kV
 - 污染等级: 3
 - 绝缘阻抗: $>10^{10}\Omega$
 - 材料: 聚酰胺
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: ≥ 500
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理: 镀银
 - 接触电阻: $\leq 0.3\text{m}\Omega$
 - 线径范围: $35-70\text{mm}^2$
 - 最大电缆直径: 18mm
 - 冷压模具: 按照 DIN 46 235
 - 压力要求: 130kN
- 固定框架:
- 材料: 不锈钢
 - 外壳固定螺丝的拧紧力矩: $0.5\text{N}\cdot\text{m}$
 - 工具: 液压钳: TL05

Technical specification:

- Insters:
- No. of contact: 1
 - Rated current: 250A
 - Rated voltage: 2000V
 - Rated impulse voltage: 12kV
 - Pollution degree: 3
 - Insulation resistance: $>10^{10}\Omega$
 - Material: polyamide
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: ≥ 500
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface: hard-silver plated
 - Contact resistance: $\leq 0.3\text{m}\Omega$
 - Wire gauge: $35-70\text{mm}^2$
 - Max. cable diameter: 18mm
 - Crimp dies: acc. to DIN 46 235
 - Pressing force requirement: 130kN
- Frame:
- Material: stainless steel
 - Tightening torque of the fixing screws: $0.5\text{N}\cdot\text{m}$
 - Tools: Manual hydraulic clamp: TL05



						表面处理 Finish		-		图号 Drawing No.		-		
						材料 Material		-		产品代号 Part Code		HC250-FC		
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date					产品料号 Part No.		1310010200001	
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name		-		
绘图 Drawn	BQ LUO	15.03.2019	标准化 Stand.	-	-	2:3	V1.1	13.4g	-					
审核 Checked	HZ LAN	15.03.2019												
工艺 Process	-	-	批准 Approved	HQ ZHANG	15.03.2019			All Dimensions in mm Original Size DIN A 4				厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.,LTD		