

型号 项目		DTB-80	D(T)B-100	D(T)B-160	D(T)B-200	D(T)B-200B
		额定输出功率	KVA	80	100	160
额定初级电	V	500	500	500	500	500
额定频率	Hz	1000	1000	1000	1000	1000
最大短路电	A	18000	28000	40000	55000	60000
负载持续率	%	25	25	25	25	25
臂伸尺寸	mm	500x240	500x240	450x260	450x260	450x260
最大压力	N	6100	6100	6100	10000	15000
电极行程	mm	75	75	100	100	120
冷却水量	L/min	8	12	12	24	35
重量	KG	300	320	400	550	1500
电极头	mm	ø16	ø16	ø16	ø20	ø20
电极握杆	mm	ø25x180	ø25x180	ø32x250	ø32x250	ø32x250
钢二块叠焊	mm	2.5+2.5	3.0+3.0	4.0+4.0	4.5+4.5	5.0+5.0
铝二块叠焊	mm	1.0+1.0	1.5+1.5	2.0+2.0	2.5+2.5	3.0+3.0
外形尺寸 (长x宽x高)	mm	1040x670x1720	1100x760x1770	1100x480x1840	1100x480x1840	1800x1030x2480

<b>D (T) B-320B</b>
320
500
1000
80000
25
450x260
24000
120
35
1600
ø25
ø40x250
6.0+6.0
3.5+3.5
1800x1030x2480