

## FT型铜镀镍防爆接头



- ☆ 产品材质:外部金属为黄铜镀镍, 夹紧爪为尼龙PA66, 密封件为改性橡胶
- ☆ 防护等级: 适用于各种普通电缆
- ☆ 防护等级: 在规定卡口范围内, 使用扁平密封圈旋紧迫紧头, 达IP68-10Bar
- ☆ 工作温度:  $-40^{\circ}\text{C} \sim +100^{\circ}\text{C}$  短时可达 $+120^{\circ}\text{C}$

订购事例: WYD-FT6-M10\*1.5

订货号 Order No.	螺纹 Thread	适配电缆 C1 clamping range mm	螺纹外径 D1 thread	螺纹长度 GL thread	机板孔径 Plate aperture	扳手径 D/A Spanner diameter mm
WYD- FT6-M10	M10*1.5	6~2	10	6	10~10.3	14
WYD-FT5-M12	M12*1.5	5.3 ~ 3	12	8	12~2.3	17
WYD-FT6S-M12		6 ~ 2	12	8	12~2.3	17/14
WYD-FT8-M12		7.8 ~ 4.5	12	8	12~2.3	17
WYD-FT6-M16	M16*1.5	7 ~ 4	16	9	16~16.3	20
WYD-FT8S-M16		7.8 ~ 4.5	16	9	16~16.3	20/17
WYD-FT10-M16		10 ~ 6	16	9	16~16.3	20
WYD-FT10-M18	M18*1.5	10 ~ 6	18	9	18~18.3	20
WYD-FT8S-M20	M20*1.5	8 ~ 5.5	20	9.5	20~20.3	24
WYD-FT10S-M20		10 ~ 6	20	9.5	20~20.3	24
WYD-FT12S-M20		12 ~ 8	20	9.5	20~20.3	24
WYD-FT14-M20		14 ~ 9	20	9.5	20~20.3	26
WYD-FT16-M25	M25*1.5	16 ~ 12	25	12	25~25.4	30
WYD-FT18-M25		18 ~ 14	25	12	25~25.4	30
WYD-FT18-M27	M27*1.5(2.0)	18 ~ 14	27	12	27~27.4	32
WYD-FT18-M30	M30*1.5(2.0)	18 ~ 14	30	12	30~30.4	34/32
WYD-FT22-M32	M32*1.5	22 ~ 16	32	12.5	32~32.4	38/40
WYD-FT25-M32		25 ~ 18	32	12.5	32~32.4	38/40
WYD-FT25-M33	M33*2	25 ~ 18	33	12.5	33~33.4	40
WYD-FT25-M36	M36*1.5(2.0)	25 ~ 18	36	12.5	36~36.4	40
WYD-FT25-M40	M40*1.5	25 ~ 21	40	15	40~40.4	50
WYD-FT30-M40		30 ~ 24	40	15	40~40.4	50
WYD-FT30-M42	M42*2.0	30 ~ 24	42	15	42~42.4	50

WYD-FT30-M48	M48*2.0	30 ~ 24	48	15	48~48.4	52/50
WYD-FT32-M50	M50*1.5	32 ~ 26	50	15	50~50.4	60
WYD-FT39-M50		41 ~ 31	50	15	50~50.4	60
WYD-FT44-M60	M60*2.0	36-44	60	15	60~60.4	70/65
WYD-FT44-M63	M63*1.5	36-44	63	15	63~63.4	70/65
WYD-FT46-M63		46 ~ 40	63	15	63~63.4	70/65
WYD-FT49-M63		51 ~ 44	63	15	63~63.4	75/70
WYD-FT44-M64	M64*1.5	36-44	64	15	64~64.4	70/65
WYD-FT52-M72	M72*2.0	42 ~ 52	50	15	72~72.5	80/75
WYD-FT66-M75	M75*2.0	66-56	75	15	75~75.6	90/85
WYD-FT77-M90	M90*2.0	77-66	90	15	90~90.6	100
订货号 Order No.	螺纹 Thread	适配电缆 C1 clamping range mm	螺纹外径 D1 thread mm	螺纹长度 GL thread mm	机板孔径 Plate aperture mm	扳手径 D/A Spanner diameter mm
WYD-FT6S-PG7	PG7	6~2	12.5	8	12.5~12.8	14
WYD-FT5-PG7		5.3 ~ 3	12.5	8	12.5~12.8	17
WYD-FT8-PG7		7.8 ~ 4.5	12.5	8	12.5~12.8	17
WYD-FT5-PG9	PG9	5.3 ~ 3	15.2	8	15.2~15.5	17
WYD-FT8-PG9		7.8 ~ 4.5	15.2	8	15.2~15.5	17
WYD-FT6-PG11	PG11	7 ~ 4	18.6	9	18.6~18.9	20
WYD-FT10-PG11		10 ~ 6	18.6	9	18.6~18.9	20
WYD-FT8-PG13.5	PG13.5	8 ~ 5.5	20.4	9.5	20.4~20.7	24
WYD-FT10- PG13.5		10 ~ 6	20.4	9.5	20.4~20.7	24
WYD-FT12- PG13.5		12 ~ 8	20.4	9.5	20.4~20.7	24
WYD-FT10-PG16	PG16	11 ~ 7	22.5	9.5	22.5~22.8	26
WYD-FT14-PG16		14 ~ 9	22.5	9.5	22.5~22.8	26
WYD-FT16-PG21	PG21	16 ~ 12	28.3	12	28.3~28.6	30
WYD-FT18-PG21		18 ~ 14	28.3	12	28.3~28.6	30
WYD-FT22-PG29	PG29	22 ~ 16	37	12.5	37~37.4	40
WYD-FT25-PG29		25 ~ 18	37	12.5	37~37.4	40
WYD-FT25-PG36	PG36	25~18	47	15	47~47.4	52/50
WYD-FT30-PG36		30~24	47	15	47~47.4	52/50
WYD-FT32-PG42	PG42	32~25	54	15	54~54.4	60
WYD-FT41-PG42		41~31	54	15	54~54.4	66/60
WYD-FT44-PG48	PG48	44~38	59.3	15	59.3~59.7	70/65
订货号 Order No.	螺纹 Thread	适配电缆 C1 clamping range mm	螺纹外径 D1 thread mm	螺纹长度 GL thread mm	机板孔径 Plate aperture mm	扳手径 D/A Spanner diameter mm
WYD-FT6-G1/4	G1/4	5.3-3	13.15	8	13.2~13.4	17
WYD-FT8-G1/4		7.8-4.5	13.15	8	13.2~13.4	17
WYD-FT5-G3/8	G3/8	5 ~ 3	16.66	9	16.7~16.9	18
WYD-FT8-G3/8		8 ~ 4	16.66	9	16.7~16.9	18
WYD-FT8-G1/2	G1/2	8 ~ 5.5	20.99	9	21~21.2	24
WYD-FT10-G1/2		10 ~ 6	20.99	9	21~21.2	24

WYD-FT12-G1/2	G1/2	12 ~ 8.5	20.99	9	21~21.2	24
WYD-FT14-G1/2		14~10	20.99	9	21~21.2	26
WYD-FT16-G3/4	G3/4	16 ~ 12	26.44	12	26.5~26.8	30
WYD-FT18-G3/4		18 ~ 14	26.44	12	26.5~26.8	30
WYD-FT25-G1	G1	25-18	33.25	12	33.3~33.6	40
WYD-FT22-G1		22-15	33.25	12	33.3~33.6	40
WYD-FT25-G1-1/4	G1-1/4	25~18	41.91	15	42~42.3	50
WYD-FT30-G1-1/4		30-24	41.91	15	42~42.3	50
WYD-FT25-G1-1/2	G1-1/2	25~18	47.8	15	48~48.4	52/50
WYD-FT30-G1-1/2		30-24	47.8	15	48~48.4	52/50
WYD-FT44-G2	G2	44-38	59.61	15	60~60.4	65
WYD-FT66-G2-1/2	G2-1/2	66-56	75.18	15	75.2~75.6	90/85
订货号 Order No.	螺纹 Thread	适配电缆 C1 clamping range mm	螺纹外径 D1 thread mm	螺纹长度 GL thread mm	扳手径 D/A Spanner diameter mm	包装数量pcs
WYD-FT5-NPT3/8	NPT3/8	5 ~ 3	17.05	8	20	50
WYD-FT8-NPT3/8		8 ~ 4	17.05	8	20	
WYD-FT8-NPT1/2	NPT1/2	8 ~ 5.5	21.22	9	24	25
WYD-FT12-NPT1/2		12 ~ 8.5	21.22	9	24	
WYD-FT16-NPT3/4	NPT3/4	16 ~ 12	26.56	12	30	20
WYD-FT18-NPT3/4		18 ~ 14	26.56	12	30	
WYD-FT25-NPT 1	NPT1	25-18	33.23	15	40	16
WYD-FT22-NPT 1		22-15	33.23	15	40	
WYD-FT25-NPT1-1/4	NPT1-1/4	25~18	41.98	15	50	9
WYD-FT30-NPT1-1/4		30-24	41.98	15	50	
WYD-FT25-NPT1-1/2	NPT1-1/2	25~18	48.05	15	52/50	
WYD-FT30-NPT1-1/2		30-24	48.05	15	52/50	
WYD-FT44-NPT2	NPT2	44~38	60.09	15	65	6