


Pin No	Symbol
1	CSB
2	RST
3	CD
4	SCK
5	SDA
6	VDD
7	VSS
8	VB0-
9	VB1-
10	VB1+
11	VB0+
12	VLCD

SCALE: 10:1



NOTES:

1. DISPLAY TYPE: FSTN/POSITIVE
2. OPERATING VOLTAGE: VOP=4.05V VDD=2.4V-3.3V
3. OPERATING TEMPERATURE: -10°C~60°C
4. STORAGE TEMPERATURE: -20°C~70°C
5. DRIVE MODE: 1/33D, 1/4B
6. VIEWING DIRECTION: 6:00
7. POLARIZER TYPE: REFLECTIVE
8. CONNECTOR: COG/UC1701e
9. CUSTOMER No.: C4072
10. FREQUENCY: 64HZ
11. Unassigned tolerances ±0.20mm

SHENZHEN RIFDA LCD CO., LTD.

TEL: +86-755-27041286, FAX: +86-755-28126726

DESIGNED BY: Zhu Yulong	VERSION: 6.0
CHECKED BY: Xing Mingying	NO. 1 OF 3
APPROVED BY: Wu Ligang	UNIT: MM
DATE: 2018-04-03	

VER.	SYMBOL	AMENDMENT	SIGN	DATE
01	△	First issue	ZHU YULONG	170704
02	△	改电压	ZHU YULONG	171017
03	△	改封口、总厚度、公差、增加VDD电压	ZHU YULONG	171024
04	△	改电压	ZHU YULONG	171123
05	△	加易撕贴	ZHU YULONG	180129
06	△	改FPC外形	ZHU YULONG	180403