



Designation: A 453/A 453M – 03

高强度紧固件专家俞文龙博客，免费提供各种
优质紧固件标准资料，提供各种优质紧固件，
具体见<http://blog.sina.com.cn/yuwenlong88>

Standard Specification for High-Temperature Bolting Materials, with Expansion Coefficients Comparable to Austenitic Stainless Steels¹

This standard is issued under the fixed designation A 453/A 453M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope*

1.1 This specification² covers four grades of bolting materials with ten classes of yield strength ranging from 50 to 120 ksi [345 to 827 MPa] for use in high-temperature service such as fasteners for pressure vessel and valve flanges. The material requires special processing and is not intended for general purpose applications. The term “bolting material,” as used in this specification, covers rolled, forged, or hot-extruded bars; bolts, nuts, screws, washers, studs, and stud bolts. Headed bolts and rolled threads may be supplied.

NOTE 1—Other bolting materials are covered by Specification A 193/A 193M and Specification A 437/A 437M.

1.2 Supplementary Requirement S 1 of an optional nature is provided. This shall apply only when specified by the purchaser in the order.

1.3 This specification is expressed in both inch-pound units and in SI units. However, unless the order specifies the applicable “M” specification designation (SI units), the material shall be furnished to inch-pound units.

1.4 The values stated in either inch-pound units or SI units are to be regarded separately as standard. Within the text, the SI units are shown in brackets. The values stated in each system are not exact equivalents; therefore, each system must be used independently of the other. Combining values from the two systems may result in nonconformance with the specification.

2. Referenced Documents

2.1 ASTM Standards:³

¹ This specification is under the jurisdiction of ASTM Committee A01 on Steel, Stainless Steel, and Related Alloys and is the direct responsibility of Subcommittee A01.22 on Steel Forgings and Wrought Fittings for Piping Applications and Bolting Materials for Piping and Special Purpose Applications.

Current edition approved Oct. 1, 2003. Published November 2003. Originally approved in 1961. Last previous edition approved in 2002 as A 453/A 453M – 02.

² For ASME Boiler and Pressure Vessel Code Applications see related Specification SA-453 in Section II of that Code.

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

- A 193/A 193M Specification for Alloy-Steel and Stainless Steel Bolting Materials for High-Temperature Service
- A 437/A 437M Specification for Alloy-Steel Turbine-Type Bolting Material Specially Heat Treated for High-Temperature Service
- A 962/A 962M Specification for Common Requirements for Steel Fasteners or Fastener Materials, or Both, Intended for Use at Any Temperature from Cryogenic to the Creep Range
- E 139 Test Method for Conducting Creep, Creep-Rupture, and Stress-Rupture Tests of Metallic Materials

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

- 3.1.1 *bolting material*—this covers rolled, forged, or hot-extruded bars; bolts, nuts, screws, washers, studs, and stud bolts; and also includes those manufactured by upset heading or roll threading techniques.
- 3.1.2 *heat-treatment charge*—one heat of material heat treated in one batch. If a continuous operation is used, the weight processed as a heat-treatment charge shall not exceed the weights in Table 1.
- 3.1.3 *lot*—a lot shall consist of the quantities shown in Table 2.

4. Ordering Information

- 4.1 The inquiry and order shall indicate the following:
 - 4.1.1 Quantity (weight or number of pieces),
 - 4.1.2 Description of material (bars, bolts, nuts, etc.),
 - 4.1.3 Grade and class (see Table 3),
 - 4.1.4 Method of finishing (see 6.1),
 - 4.1.5 Type of thread desired (see 6.1.1),
 - 4.1.6 Alternative test method option (see 7.2.4.3),
 - 4.1.7 Bolt shape option, if any,
 - 4.1.8 Thread option, if any,
 - 4.1.9 Test method for surface quality, if any,
 - 4.1.10 Test location option, if any,
 - 4.1.11 Rejection option, if any, and
 - 4.1.12 If stress-rupture testing is not required, except for Grade 660 Class D (see 7.2.1).

*A Summary of Changes section appears at the end of this standard.

TABLE 1 Continuous Heat-Treatment Charge Sizes

Diameter, in. [mm]	Weight, lb [kg]
To 1¼ [44]	3000 [1400]
Over 1¼ [44] to 2½ [63]	6000 [2700]
Over 2½ [63]	12000 [5400]

TABLE 2 Lot Sizes

Diameter, in. [mm]	Maximum Lot Size, lb [kg]
1½ [38] and under	200 [90]
Over 1½ [38] to 1¾ [44], incl	300 [140]
Over 1¾ [44] to 2½ [63], incl	600 [270]
Over 2½ [63]	20 pieces

5. Common Requirements

5.1 Material and fasteners supplied to this specification shall conform to the requirements of Specification A 962/A 962M. These requirements include test methods, finish, thread dimensions, marking, certification, optional supplementary requirements, and others. Failure to comply with the requirements of Specification A 962/A 962M constitutes nonconformance with this specification. In case of conflict between the requirements of this specification and Specification A 962/A 962M, this specification shall prevail.

6. Materials and Manufacture

6.1 Finishing Process:

6.1.1 Threads may be performed by machining or rolling. For Type 1 bolting, threading shall be performed after precipitation heat treatment. Types M1 and M2 bolting shall have machine cut threads. For Types 2 R1 and R2, bolting shall have rolled threads. Types R1 and M1 bolting, threading shall be performed after precipitation heat treatment. Types R2 and M2 bolting shall be threaded after solution heat treatment but prior to precipitation heat treatment. When not specified by the purchaser, the type supplied shall be the option of the manufacturer.

6.2 Heat Treatment—Each grade and class shall be heat treated as prescribed in Table 4.

7. Mechanical Properties

7.1 Tension Test:

7.1.1 Requirements—The material in each heat-treatment charge shall conform to the room-temperature tensile requirements in Table 5.

7.1.2 Number of Specimens:

7.1.2.1 Heat-Treated Bars—When not more than two sizes of bars are heat treated in the same load, one tension test shall be made from each size in each heat of material in the heat-treatment charge (see 3.1.2). When more than two sizes of bars are treated in the same charge, one tension test shall be made from one bar of each of the two largest diameters from each heat of material in the heat-treating charge.

7.1.2.2 Finished Parts—One tension test shall be made if the lot consists of parts of the same nominal diameter. If the lot consists of parts of more than one nominal diameter, one tension test shall be made from each nominal diameter of each heat involved in the lot (see Section 3).

7.1.2.3 The diameter range shall be in increments of ½ in. [12.5 mm].

7.2 Stress-Rupture Test:

7.2.1 Requirements—The material shall conform to the stress-rupture requirements prescribed in Table 6 for design temperatures above 800°F [427°C]. Material not stress-rupture tested shall be permanently stamped NR. Grade 660 Class D does not require stress-rupture and shall be stamped NR.

7.2.2 The number of specimens shall be the same as the required number of tension test specimens.

7.2.3 The test location and orientation shall be the same as that required for the tension test specimens.

7.2.4 Test Method:

7.2.4.1 The rupture test shall be performed in accordance with Practice E 139.

7.2.4.2 A combination smooth and notched test specimen, machined to the dimensions prescribed in Fig. 1 and Table 7, shall be tested in accordance with the stress-rupture requirements prescribed in Table 6. The test shall be continued to rupture. The rupture shall occur in the smooth section of the bar.

7.2.4.3 As an alternative procedure and, when specifically approved by the purchaser, separate smooth and notched test specimens, machined from adjacent sections of the same piece, with gage sections conforming to the respective dimensions of Table 7, may be tested under the above conditions. The notched specimen need not be tested to rupture but shall not rupture in less time than the companion smooth specimen.

7.2.4.4 When the minimum specified time to rupture in Table 6 has been achieved, incremental loading may be used to accelerate the time to rupture. At intervals of 8 to 16 h, preferably 8 to 10 h, the stress shall be increased in increments of 5000 psi [34.5 MPa]. Rupture location, and elongation requirements shall be as prescribed in Table 6, 7.2.4.2, and 7.2.4.3.

7.3 Hardness Test:

7.3.1 Requirements—The material shall conform to the room temperature hardness requirements prescribed in Table 5. For Grade 660 Class D, in the case of conflict, tensile test results shall prevail over minimum hardness.

7.3.2 Number of Tests:

7.3.2.1 Bars 2 in. [50 mm] and Over—One test on each mill-treated length.

7.3.2.2 Bars under 2 in. [50 mm]—One test on at least 10 % of the mill treated lengths.

7.3.3 Test Locations—The hardness test shall be made at the center of the cross section for bars up to 1 in. [25 mm] in diameter, and at the midradius on bars 1 in. [25 mm] and larger in diameter.

8. Product Marking

8.1 Bolts, Nuts, Screws, Studs, and Steel Bolts—In addition to the grade and class shown in Table 4, the type designation (see 6.1.1) shall also appear on all bolting material so processed. Grade 660 Class D shall be stamped NR in addition to other required markings.



TABLE 3 Chemical Requirements

		Grade 660		Grade 651	
UNS Number		S66286		S63198	
	Content, %	Product Analysis Variation, Over or Under, %	Content, %	Product Analysis Variation, Over or Under, %	
Carbon	0.08 max	0.01 over	0.28–0.35	0.02	
Manganese	2.00 max	0.04	0.75–1.50	0.04	
Phosphorus	0.040 max	0.005 over	0.040 max	0.005 over	
Sulfur	0.030 max	0.005 over	0.030 max	0.005 over	
Silicon	1.00 max	0.05	0.30–0.80	0.05	
Nickel	24.0–27.0	0.20	8.0–11.0	0.15	
Chromium	13.5–16.0	0.20	18.0–21.0	0.25	
Molybdenum	1.00–1.50	0.05	1.00–1.75	0.05	
Tungsten	1.00–1.75	0.05	
Titanium	1.90–2.35	0.05	0.10–0.35	0.05 over	
Columbium ^A	0.25–0.60	0.05	
Aluminum	0.35 max	0.05 over	
Vanadium	0.10–0.50	0.03	
Boron	0.001–0.010	0.0004 under to 0.001 over	
Copper	0.50 max	0.03 over	

		Grade 662		Grade 665	
UNS Number		S66220		S66545	
	Content, %	Product Analysis, Variation Over or Under, %	Content, %	Product Analysis Variation, Over or Under, %	
Carbon	0.08 max	0.01 over	0.08 max	0.01 over	
Manganese	0.40–1.00	0.03	1.25–2.00	0.04	
Phosphorus	0.040 max	0.005 over	0.040 max	0.005 over	
Sulfur	0.030 max	0.005 over	0.030 max	0.005 over	
Silicon	0.40–1.00	0.05	0.10–0.80	0.05	
Nickel	24.0–28.0	0.20	24.0–28.0	0.20	
Chromium	12.0–15.0	0.15	12.0–15.0	0.15	
Molybdenum	2.0–3.5	0.10	1.25–2.25	0.10	
Titanium	1.80–2.10	0.05	2.70–3.3	0.05	
Aluminum	0.35 max	0.05 over	0.25 max	0.05 over	
Copper	0.50 max	0.03 over	0.25 max	0.03 over	
Boron	0.001–0.010	0.0004 under to 0.001 over	0.01–0.07	0.005	

^A Or columbium plus tantalum.

TABLE 4 Heat Treatment Requirements^A

Grade	Class	Solution Treatment	Hardening Treatment
660	A	1650 ± 25°F [900 ± 14°C], hold 2 h, min, and liquid quench	1325 ± 25°F [720 ± 14°C], hold 16 h, air cool
	B	1800 ± 25°F [980 ± 14°C], hold 1 h, min, and liquid quench	1325 ± 25°F [720 ± 14°C], hold 16 h, air cool
	C	1800 ± 25°F [980 ± 14°C], hold 1 h min, and oil quench	1425 ± 25°F [775 ± 14°C] hold 16 h, air cool
651	D	1650 ± 25°F [900 ± 14°C], hold 2 h min, and liquid quench or 1800 ± 25°F [980 ± 14°C], hold 1 h min, and liquid quench	1200 ± 25°F [650 ± 14°C] hold 16 h, air cool 1325 ± 25°F [720 ± 14°C], hold 16 h, air cool If necessary to achieve properties, second age: 1200 ± 25°F [650 ± 14°C] hold 16 h, air cool
	A		hot-cold worked at 1200°F [650°C] min with 15 % min reduction in cross-sectional area, stress-relief anneal at 1200°F [650°C] min or 4 h, min
662	B		hot-cold worked at 1200°F [650°C] min with 15 % min reduction of cross-sectional area, stress-relief anneal at 1350°F [730°C] min for 4 h, min
	A	1800 ± 25°F [980 ± 14°C], hold 2 h, liquid quench	1350 to 1400°F [730 to 760°C], hold 20 h, furnace cool to 1200 ± 25°F [650 ± 14°C], hold 20 h, air cool
665	B	1950 ± 25°F [1065 ± 14°C], hold 2 h, liquid quench	1350 to 1400°F [730 to 760°C], hold 20 h, furnace cool to 1200 ± 25°F [650 ± 14°C], hold 20 h, air cool
	A	1800 ± 25°F [980 ± 14°C], hold 3 h, liquid quench	1350 to 1400°F [730 to 760°C], hold 20 h, furnace cool to 1200 ± 25°F [650 ± 14°C], hold 20 h, air cool
	B	2000 ± 25°F [1095 ± 14°C], hold 3 h, liquid quench	1350 to 1400°F [730 to 760°C], hold 20 h, furnace cool to 1200 ± 25°F [650 ± 14°C], hold 20 h, air cool

^A Times refer to the minimum time material is required to be at temperature.

9. Keywords

9.1 bolts–steel; fasteners–steel; marking; nuts–steel; pre-precipitation hardening steels; pressure vessel service; revision

letter; steel bars–alloy; steel bolting material; steel flanges; steel valves; temperature service applications–high; year date

 **A 453/A 453M – 03**

TABLE 5 Mechanical Property Requirements

Grade	Class	Tensile Strength, min		Yield Strength (0.2 % Offset), min		Elongation in 4× Diam, min, %	Reduction of Area, min, %	Brinell Hardness Number	Approximate Rockwell Hardness, B and C	
		ksi	MPa	ksi	MPa				min	max
660	A, B, and C	130	895	85	585	15	18	248–341	24 HRC	37 HRC
	D	130	895	105	725	15	18	248–321	24 HRC	35 HRC
651	A	100	690	70 ^A	485	18	35	217–277	95 HRB	29 HRC
	B	95	655	60 ^B	415	18	35	212–269	93 HRB	28 HRC ^C
662	A	130	895	85	585	15	18	248–321	24 HRC	35 HRC ^C
	B	125	860	80	550	15	18	248–321	24 HRC	35 HRC
665	A	170	1170	120	830	12	15	311–388	32 HRC	41 HRC
	B	155	1070	120	830	12	15	311–388	32 HRC	41 HRC

^A Material sizes 3 in. [76 mm] and under in diameter.

^B Material sizes over 3 in. [76 mm] in diameter.

^C Conversion numbers taken from Specification A 193/A 193M, Table number 2 (austenitic steels); others by interpolation.

TABLE 6 Stress Rupture Requirements

Grade	Class	Test Temperature, °F [°C]	Stress, min		Time to Rupture, min, h ^A	Elongation, min, %
			ksi	MPa		
660	A, B, and C	1200 [650]	56	385	100	5
651	A and B	1200 [650]	40	275	100	5
662	A and B	1200 [650]	55	380	100	5
665	A	1200 [650]	75	515	100	3
	B	1200 [650]	70	485	100	5

^A The combination bar specimen shown in Fig. number 1 shall be tested continuously at the temperature and at the minimum stress specified or at a greater stress and shall rupture in a time not less than that specified.

高强度紧固件专家俞文龙博客，免费提供各种
优质紧固件标准资料，提供各种优质紧固件，
具体见<http://blog.sina.com.cn/yuwenlong88>

ASME A 453/A 453M - 03




FIG. 1 Combination Smooth-Notch Stress-Rupture Test Specimen
(See Table 6)

TABLE 7 Test Specimen Dimensions

- NOTE 1—Surfaces marked⁸, finish to 8 μ in. [0.2 μ m] rms or better.
 NOTE 2—The difference between dimensions F and D shall not exceed 0.0005 in. [0.01 mm] for specimens 1 or 2. The difference shall not exceed 0.001 in. [0.02 mm] for specimens 3, 4, 5, or 6.
 NOTE 3—Taper the gage length G to the center so that the diameter D at the ends of the gage length exceeds the diameter at the center of the gage length by not less than 0.0005 in. [0.01 mm] nor more than 0.0015 in. [0.04 mm].
 NOTE 4—All sections shall be concentric about the specimen axis within 0.001 in. [0.02 mm].
 NOTE 5—Thread size T shall be equal to or greater than diameter H .
 NOTE 6—Dimensions A and B are not specified.
 NOTE 7—Length of shoulder C — $\frac{1}{8} + \frac{1}{32} - 0$ in. [3.2 + 0.8 mm].
 NOTE 8—Length of shoulder E — $\frac{3}{8} + \frac{1}{32} - 0$ in. [10.0 + 0.8 mm].

Specimen Type	Mid-length Gage Dia D and Notch-Root Dia F		Gage Length, G	Shoulder Diameter, H	Notch-Root Radius
Inches					
1	0.125	0.125	0.5	0.177	0.005
2	0.160	0.160	0.65	0.226	0.005
3	0.178	0.178	0.75	0.250	0.005
4	0.252	0.252	1.0	0.375	0.007
5	0.357	0.357	1.5	0.500	0.010
6	0.505	0.505	2.0	0.750	0.015
Tolerance	± 0.001	± 0.001	± 0.05	± 0.003	± 0.0005
Millimetres					
7	3.17	3.17	12.0	4.5	0.13
8	4.06	4.06	17.0	5.5	0.13
9	4.52	4.52	20.0	6.5	0.13
10	6.40	6.40	25.0	9.5	0.18
11	9.07	9.07	40.0	12.0	0.25
12	12.8	12.8	50.0	19.0	0.38
Tolerance	± 0.025	± 0.025	± 1.3	± 0.1	± 0.01

高强度紧固件专家俞文龙博客，免费提供各种
 优质紧固件标准资料，提供各种优质紧固件，
 具体见<http://blog.sina.com.cn/yuwenlong88>

TABLE 8 Permissible Variations in Size of Cold-Finished Bars

Specified Size, in. [mm]	Permissible Variations from Specified Size, in. [mm] ^A	
	Over	Under
Over ½ to 1 [13 to 25], excl	0.002 [0.05]	0.002 [0.05]
1 to 1½ [25 to 38], excl	0.0025 [0.06]	0.0025 [0.06]
1½ to 4 [38 to 100], incl ^B	0.003 [0.08]	0.003 [0.08]

^A When it is necessary to heat treat or heat treat and pickle after cold finishing, because of special hardness or mechanical property requirements, the permissible variations are generally double those shown in the table.

^B For size tolerances of sizes over 4 in. [100 mm], the manufacturer should be consulted.

SUMMARY OF CHANGES

Committee A01 has identified the location of selected changes to this standard since the last issue (A 453/A 453 – 02) that may impact the use of this standard..

(1) Revised 4.1.12, 7.2.1, 7.3.1, and 8.1 to include Grade 660 Class D. (2) Corrected Hardness to Tensile conversions in Table 5.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).

高强度紧固件专家俞文龙博客，免费提供各种
优质紧固件标准资料，提供各种优质紧固件，
具体见<http://blog.sina.com.cn/yuwenlong88>

需要更多免费电子书籍，可以联系邮箱:694800950@qq.com，注明：求索免费书籍

参考信息：一些产品和服务信息及可以免费下载的书籍

看空手赚钱项目大全，做新时代的致富高手

空手赚钱项目大全——一本看了做了就能马上赚钱的书

目前社会不是没有钱，不是没有项目，也不是没有钱可以赚，之所以没有赚到钱，是没有用对的思维、对的方法做对的事情。

《空手赚钱项目大全》就是一本让人看了就能马上赚到钱的书，当然，还有一个条件是要去做，书中要好多项目都是不需要投资可以赚大钱的，当然关键是要去做，有了好的点子，好的项目，如果不去做，也是赚不了钱的。

书中有很多好的项目只要去做了，是可以实实在在赚到钱的，甚至是大钱的。有的项目是灰色和半灰色的，互帮互助创富顾问俞文龙认为对于灰色和半灰色的项目，我们只学习思路，仅供借鉴，碰到类似事情不上当受骗，不建议大家去做，毕竟有的事情做了，就有可能触犯法律，赚了钱却没有化钱的命，也是我们不推荐的。

空手赚钱项目大全不含封面是 158 页，129 个项目，有正规项目，偏门项目，防骗项目，违法项目。书价格 188 元/本。

空手赚钱项目大全——一本看了做了就能马上赚钱的书具体目录、介绍(含几个小项目)下载地址 <http://pan.baidu.com/s/1c5mlVw>

对此大全感兴趣者请联系咨询热线：电话/微信 13600632303，QQ：694800950。

互帮互助创富群 VIP 会员

终生会员费 688 元，一年内赚不回 1000 元以上，可以 688 元全退。

立足本职工作，充分挖掘和利用自己已有的技能和资源，通过互帮互助，获得更多的财富，朋友，快乐和幸福。

尺有所短，寸有所长。现在社会是一个分工合作的社会，也是一个各有所长的社会。懂营销的不会开发产品，没有看优秀产品的能力，能开发新产品的没有制作能力，有制作能力的，未必懂生产管理，懂生产管理的，未必有融资能力。。。大家单打独斗，各顾各战斗，也许都是一条虫，如果大家团结在一起，各自发挥所长，也许都是一条龙。

没成功是因为缺少能力吗？不是，能力大部分应该是有的，也够了；没成功是因为缺少资源？不是，每个人都有资源；那不成功是什么原因？——缺少一个互帮互助，各尽所能的团队。大家的技能和资源没有充分利用出来，只要充分利用出来了我们的技能和资源，我们都会过得更好。

大家没有更大的成功，是因为大家都只看着自己面前的一亩三分田地，根本没有想过要立足本职工作，充分挖掘和利用自己的所有技能和资源，通过互帮互助，技能互补，资源互助，收获更多，改变更多。

每个人都有自己的技能，每个人都有独一无二的经验，每个人都有相应的资源，要么是没有想到要利用，要么是一个人不能充分利用。如果自己的技能、经验和资源，充分利用，也许会改变自己的人生，最起码，也会过得比现在好。只是很多人利用不出来，这中间就缺少一个资源互助，技能互补，互帮互助的团队。

如果能出点子的出点子，能够营销的帮助营销，能够开发产品的开发产品，那整个团队里的人都能更富裕更幸福。如果更多这样的团队，人民就会更富裕，更幸福。

对此项目感兴趣者请联系咨询热线：电话/微信 13600632303，QQ：694800950。
相关介绍见互助创富第一期和第二期。

互助创富第一期下载地址：

链接：<https://pan.baidu.com/s/1Zn3Ysqfd2JWNHf3MvZEdoQ> 提取码：nxxu

互助创富第二期.pdf 下载地址：

链接：https://pan.baidu.com/s/1an0qaldIon9X-Ny_HvGtgg 提取码：5w26

不需投入很多精力和时间每月多赚 600 至数千的红包项目

1、只要一只手机，一个微信，在不耽误正常工作的情况下，前期只要简单的操作，后期只要正常维护，一般每月可赚钱 600 元以上，如果玩得好，可以每月赚几千元。

2、当然，如果配上其他的收红包方式，一只手机可以相当于赚一个月工资。

3、为什么要转让？

因为一只手机一个微信就赚 600 至数千元，我还有更大的目标和事情要做，而且转让了这项目也不影响我自己操作。

4、这是我自己实操摸索出来的项目。

5、适合所有赚钱不多、想多赚点零化钱的人，特别适合带小孩的宝妈，坐店的人，及一些办公室文员，还有就是放学后的学生，甚至能操作的老大爷老大妈。

6、项目永远不会过时。

7、对此项目感兴趣者请联系咨询热线：电话/微信 13600632303，QQ：694800950。

超低价提供打印、复印、书本装订

复印：每张 A4 纸 0.11~0.30 元；

打印：每张 A4 纸 0.18~0.40 元；（打字排版自己负责）

书本装订（塑胶装订）：每本五元（150 张纸以内）

单次打印或复印 500 页以上，来回邮费（或快递费）自负。

同时提供光盘刻录服务。

有意者联系：QQ:694800950 电话:13600632303 俞文龙

原则上：

双面复印 A4 0.22 元/张（正反面都印）

单面复印 A4 0.15 元/张

双面打印 A4 0.40 元/张（正反面都印）

单面打印 A4 0.25 元/张

重大刑事案件可以提供高等级咨询

浙江省范围内重大刑事案件可以提供高等级咨询。当然，付出的费用也是会很高的。另外，不是每个付得起咨询费的人都有机会的，需要预约，不保证一定能获得预约名额。

（电话/微信：13600632303，QQ/微信：694800950）

军工企业，大型船厂可以有偿帮助认识相关领导，帮助入供应商网络。

军工企业，大型船厂可以有偿帮助认识相关领导，帮助入供应商网络。

（电话/微信：13600632303，QQ/微信：694800950）

提供自动化设计，电源设计

提供自动化设计，特别是 PLC 设计，单片设计，电路设计，电源设计，计算机程序设计等等。

（电话/微信：13600632303，QQ/微信：694800950）

投资 2000 万（流动资金），起码纯赚上亿实业项目

投资：2000 万（流动资金）

回报：起码上亿，而且能做成产业，长期回报项目。前期较暴利，后期稳利。

项目：实业

产业：紧固件

形式：贸易型

操作：操作简单，前期垄断，后期也稳赚

厂房：只需要仓库

机器设备：外加工，慢慢可以发展自己加工也可以。

（电话/微信：13600632303，QQ/微信：694800950）

年赚 10 万项目，只要努力去做，年赚 10 万根本不成问题

年赚 10 万项目，操作简单，前期需要努力，后期坐收渔利就可以了。项目价格 500 元。购买前不提供咨询。

（电话/微信：13600632303，QQ/微信：694800950）

简单操作，年赚 15 万项目，傻瓜式项目

年赚 15 万项目，前期操作比较辛苦，需要努力，后期就自己会来钱。项目价格 688 元。免费加入免费赚钱 VIP 群。只要去做，保证赚钱，而且操作很简单。购买前不进行咨询。

（电话/微信：13600632303，QQ/微信：694800950）

年赚 30 万项目，一旦发展得好，后期败絮其中几百万也有可能

年赚 30 万项目，前期操作比较辛苦，需要努力，还需要建立团队，贡献价值，后期还需要维护团队。主要靠团队共同努力推广产品或者服务赚钱，年赚 30 万应该没有问题。项目价格 1688 元。免费加入免费赚钱 VIP 群。只要去做，保证赚钱，而且操作很简单。购买前不进行咨询。

（电话/微信：13600632303，QQ/微信：694800950）

有偿提供点子，根据点子价值自愿付费

可以把生活中，工作中，心理上，创业中等等各种难题发给我，帮助解决，根据点子价值，自愿付费，后续服务费用另谈。

点子的价值不容忽视，有时一条点子可以解决一个大难题。

（电话/微信：13600632303，QQ/微信：694800950）

有偿帮助中小学家长提供小发明小创造点子，设想，发明方面的电子书

现在国家对小发明小创造很重视，对于小创造小发明获得相应的奖励的可以自主招生进各种名牌大学以及高考减分，获得相应专利或者小发明奖励的学生高校招生也会优先录取。

可以有偿帮助中小学家长提供小发明小创造点子，设想，发明方面的电子书。

对小发明方面深有研究，曾经在大学成立发明协会，曾经有指导的学生在小发明比赛中获奖。

（电话/微信：13600632303，QQ/微信：694800950）

提供紧固件产品销售及紧固件转型、新开、采购咨询顾问服务

紧固件咨询顾问俞文龙（电话/微信：13600632303，QQ/微信：694800950）从事螺丝行业十多年，在螺丝行业从事过技术，质检，质保，采购，业务等，积累了丰富的行业经验，积累了大量的技术资料，客户资料，供货商资料。紧固件咨询顾问俞文龙提供有偿咨询顾问服务，提供标准咨询，客户定位，产品定位咨询，提供供货商资料，提供业务开展办法咨询，提供螺丝行业一切相关事宜的有偿咨询和顾问服务。

一、向各紧固件使用单位、经销单位提供紧固件采购咨询、顾问服务；

- 二、提供紧固件企业石化紧固件转向、新开咨询、顾问服务；
 - 三、销售各种紧固件，特别是高强度紧固件；
 - 四、提供紧固件标准、资料、书籍的销售和编写；
 - 五、提供网络营销培训；
 - 六、协助提供管理、营销、销售、宣传、策划方案的设计，以提高管理效果，提高营销或销售额，提高宣传效果，以期获得较大的改观和提升。
 - 七、紧固件碰到的难题，质保书的制作，投标文件的制作，文件的制作等等各种紧固件问题，特别是高强度紧固件问题的咨询。
 - 八、有偿提供紧固件标书制作及标书制作培训及经验分享。有偿提供螺栓破坏扭矩测试报告，螺栓头部坚固性测试报告，协助制作螺栓破坏扭矩测试报告，螺栓头部坚固性测试报告。有偿提供各种紧固件原材料质保书，制作各种紧固件质保书样本和培训。
- 联系（电话/微信：13600632303，QQ/微信：694800950）

销售紧固件（螺柱、螺栓、螺母等）

产品系列：螺栓、螺柱、螺帽、螺丝、螺母、紧固件、标准件、非标件；

国内标准：GB/T901, SH3404, HG/T20613, HG/T20634, JB/T4707, NB47027, GB/T5782, GB5/T783, GB/T6170, GB/T6175, GB/T898, GB/T899 等等。

材料：35#, 45#, 25#, 35CrMoA, 30CrMoA, 25Cr2MoVA, 20MnTiB, 40Cr, 304, 316, GH2132 等。

国外标准：

美

标

（ASME/ANSI）：B1.1, B18.2.1, B18.2.2, A325, A193, A194, A490, A320, A307 德标（DIN）：DIN975, DIN931, DIN933, DIN934, 英标（BS），日标 JIS, 国际标准 ISO：ISO4014, ISO4017, ISO4032, ISO4034 等等

材料：

A193-B7/A194-2H, A193-B8/A194-8, A193-B8M/A194-8M, A193-B8C12, A193-B8MC12, A320-L7/A194-4, A320-B8/A194-8, A320-B8M/A194-8M, A307B/A563, A453-660B, A325, A490, A193M-B7/A194M-

2H, A193M-B8/A194M-8, A193M-B8M/A194M-8M, A193M-B8C12, A193M-B8MC12, A320M-L7/A194M-4/A194M-7, A320M-B8/A194M-8, A320M-B8M/A194M-8M, A307M/A563M, A453-660B, A325M, A490M 等等。

免费下载书籍：

互助创富第一期下载地址：

链接：<https://pan.baidu.com/s/1Zn3Ysqfd2JWNHf3MvZEdoQ> 提取码：nxxu

互助创富第二期.pdf 下载地址：

链接：https://pan.baidu.com/s/lan0qaldIon9X-Ny_HvGtgg 提取码：5w26

紧固件企业——如何办更赚钱，紧固件客户——如何采购更物美价优.pdf 下载地址：链接：

https://pan.baidu.com/s/liuoP01UEKTgDgSxiv_TJ1A 提取码：d3se

需要更多免费电子书籍，可以联系邮箱:694800950@qq.com，注明：求索免费书籍

免费书籍下载地址 1

1、福报与赚钱

免费下载链接: <https://pan.baidu.com/s/19Xwi3wcjckDbVM Dte EXA>

提取码: c2gt

2、公制、美制和英制螺纹标准手册 (第三版)

免费下载链接: <https://pan.baidu.com/s/1RNX VOGclV0Iioddg7QoSQ>

提取码: xsjm

3、赠品营销秘籍

免费下载链接: https://pan.baidu.com/s/1AL5VJluAcsUZ0A1gckI_dw

提取码: qyu2

4、远离高压线——建立防骗防坑的多重防火墙

免费下载链接: <https://pan.baidu.com/s/16MwQZu6R09 CTXbcJE0IIA>

提取码: v55w

5、故事会 2019 第 06 期

免费下载链接: <https://pan.baidu.com/s/1toRIODlnbVyvyXnPrnP7ZQ>

提取码: eejz

6、亮剑

免费下载链接: <https://pan.baidu.com/s/1WWDw.j6wt5YVch8Wt103y0A>

提取码: biah

7、企业资源整合详细步骤

免费下载链接: <https://pan.baidu.com/s/1VoE0vuS756IqvlwdNUW3-w>

提取码: cjat

8、资源与钱

免费下载链接: https://pan.baidu.com/s/1nqY-Lh_0mHzVAF7c0f0tDQ

提取码: 16wa

9、互助创富第一期目录及下载地址

目录

为什么要互帮互助，共同创富

为什么我们不富裕？

我们为什么要有自己的团队

当改变自己时，一切都开始改变了

空手赚钱项目大全——一本看了就能马上赚到钱的书

不需投入很多精力和时间每月多赚 600 至数千的红包项目

《我是一切的根源》
100 个创业骗人项目
警惕游医卖假药骗术
找中介买(租)房避免受骗三诀
《城市地摊财富秘籍》
【特效治疗感冒的食疗 7 方】
8 种白手起家项目
KTV 营销如何轻松打败竞争对手
每个人都还有未用的资源，有的资源利用出来就会影响一生，改变一生的命运
每个人都需要智库，你的智库在哪里？
朋友致富法
特长致富法
打工者如何赚大钱
为什么我们是穷人，而不是富人？
一次偶然事情也许就改变一个人的命运——谈人生的不确定性
赚钱智慧—小点子让你多赚钱
创业点子—彩色饺子赚大钱
让你轻送赚大钱的英语酒吧
水晶饺子制作教材
车牌牙签肉原始配方
古兰州拉面绝密配方
筹集创业资金的几个办法

互助创富第一期下载地址：

链接：<https://pan.baidu.com/s/1Zn3Ysqfd2JWNHf3MvZEdoQ> 提取码：nxxu

10、互助创富第二期目录及下载地址

目 录

为什么要互帮互助，共同创富
为什么我们不富裕？
我们为什么要有自己的团队
百度网盘账号出租，日入 100+的小项目！
支付宝赚钱 7 个模式，月入 1 万其实超简单
这些赚钱路子，你知道几条？
你和成功之间只有一个机遇的距离
空手赚钱项目大全——一本看了就能马上赚到钱的书
不需投入很多精力和时间每月多赚 600 至数千的红包项目
3 个实用致富技术
10 个新兴产业创业项目 赚钱的香饽饽
长期可操作项目，利用大学生招聘求职市场，轻松月赚 20000+
100 个创业骗人项目（第二辑）
《城市地摊财富秘籍》

寿命计算器

一女子公开她的特效美容美白秘诀(简单实惠特效)

食物酸碱一览表

山楂茶让你速减 15 斤

每个人都还有未用的资源，有的资源利用出来就会影响一生，改变一生的命运

每个人都需要智库，你的智库在哪里？

银行信用卡逾期怎么破

怎样办理大额信用卡

你的财富在哪里？

人生资源主要有哪几种

打工者如何赚大钱

只靠死工资生活的观念已经过时！年轻人发展副业是潮流！

12 堂超级搜索术，快速找到你想找的任何信息！资源！人脉！-

利用大多数人失眠的痛点，操作这个暴利偏门项目月赚两万起

小偷盗窃反为蛋糕店带来 300 万盈利，营销侧关键是做对了这

这样经营一家早餐店 轻松做到月入过万

一个关于“鸟”的赚钱项目，本是兼职却买了别墅！

筹集创业资金的几个办法

欢迎加入互帮互助创富群

互助创富第一期目录及下载地址

互助创富第二期.pdf 下载地址：

链接：https://pan.baidu.com/s/1an0qaldIon9X-Nv_HvGtgg 提取码：5w26

11、紧固件企业一如何办更赚钱，紧固件客户一如何采购更物美价优目录及下载地址

目录

石化紧固件还是可以大有作为的

怎么办好螺丝螺母厂

紧固件企业要发展，定位是基础，管理是关键

石化紧固件生产情况分析

开个螺丝厂大概要多少钱？

从我们公司看紧固件形势一片大好

紧固件咨询顾问俞文龙可以提供的服务和产品

坏事也许是好事，就看你怎么去对待，学到什么教训

怎么样做好企业？

什么公司需要大量订购螺丝，螺母，非标准件定制

谈谈紧固件企业要有自己专业的紧固件电子图书馆的理由

紧固件企业，你有自己专业的电子图书馆了吗

提供紧固件咨询顾问服务

什么叫专家？专家都是用血的代价换来的

好员工为何弃我们而去

第三只眼谈企业管理——每个企业都存在很大的提升空间

如何做一个优秀的紧固件采购？

怎么采购紧固件？

教你怎么采购紧固件

赚钱与省钱

高强度螺丝标准件质检哪些数据

用紧固件的企业需要紧固件专业顾问

生产厂家产品价格比经销商还高正常吗？

采购紧固件更要有紧固件咨询顾问

一次客户无意中发错的信息，成就了我一个十来万的合同

客户报价张冠李戴，50套螺栓损失接近8000元

提供紧固件专业电子图书馆——提供紧固件相关标准，书籍及工艺文件

紧固件技术培训教材

第八版《IFI 英制紧固件标准手册》目录

关于美标紧固件标准 ASTM A325 和 ASTM A325M

ANSI ASME IFI ASTM 这几个类型的美标标准，每个标准有没有主要的侧重点，或者使用范围，在具体的产品标准方面有没有差异，这四个标准有没有可以通用的。

开紧固件贸易公司需要注意什么呢，要多少钱呢

开螺丝店都有什么要求

刚开螺丝店怎样和老店竞争

互助创富第一期目录及下载地址

互助创富第二期目录及下载地址

紧固件企业——如何办更赚钱，紧固件客户——如何采购更物美价优.pdf 下载

地址：链接：https://pan.baidu.com/s/liuoP01UEKTgDgSxiv_TJ1A

提取码：d3se